



M / S . N.R. RUBBER INDUSTRIES.

7 SOUTH TANGRA ROAD, KOLKATA – 700046. INDIA.

Mob: 94330 98940, 98743 19408

Email: nr.rubber@yahoo.com Web: www.nrrubberindustry.com

CORK SANDWICH RUBBER PAD

MODEL NO. NRCSR – 105



MODEL	SIZE (Inches)
NRCSR – 105	18" X 18" X 7/8"
NRCSR – 105 - A	12" X 12" X 7/8"
NRCSR – 105 - B	8" X 8" X 7/8"
NRCSR – 105 - C	6" X 6" X 7/8"
NRCSR – 105 - D	4" X 4" X 7/8"
NRCSR – 105 - E	3" X 3" X 7/8"
NRCSR – 105 - F	2" X 2" X 7/8"

APPLICATION

- Wherever bolting is to be avoided non-critical vibration conditions exist. (pumps, motors, air-conditioning unit's, generators etc.)
- Recommended for acoustic problem application

NOTES

1. Material: Natural Rubber / Neoprene - S/A – $55^{\circ} \pm 5^{\circ}$
2. Type (1) :- 8 mm thickness Rib Rubber Sheet (High & Low) + Low Density Cork - 6 mm thickness in center + Rib Rubber Sheet (High & Low) - 8 mm thickness.
3. Type (2) :- 6 mm thickness Rib Rubber Sheet + Low Density Cork 10 mm thickness in center + Rib Rubber Sheet 6 mm thickness
4. Maximum loading: 60 lbs/sq.in.
5. Working range: 15 to 55 lbs/sq.in.

FEATURES

- Simple field installation.
- Excellent sound attenuation capability.
- No bolting required.